



CHILLER 200KW

TECHNICAL SPECIFICATIONS

ELECTRIC

Electrical supply:	400V/3Ph/50Hz
Type of electrical connection:	4G50
Max. power consumption:	90.9 kW
Protection class:	IP 54
Recommended fuse:	125 A

WATER CIRCUIT

Internal Pump:	3 bar
Pump capacity:	56 m³/h
Water connections:	4" Bauer
Internal Buffer Tank:	678 L

DIMENSIONS AND WEIGHT

Length:	3900 mm
Width:	1350 mm
Height:	2260 mm
Empty weight:	2780 kg
Forklift Distance:	900 mm

SOUND PRESSURE LEVEL

Soundpressure at 10m:	62 dB(A)
-----------------------	----------

ACCESSORIES



4" Bauer-connections



4" water hose



Buffer tank



External Pump



Heat exchange unit



Safety frame

EQUIPMENT



50mm² cable eye



Mobile usability



Plug-and-play System



Low Noise



Service & Leaking tests



24/7 support



Capacity: 6,7 - 1500 kW



Fast Delivery


CHARACTERISTICS



Mobile usability



Plug-and-play System



Low Noise



Service & Leaking tests



24/7 support



Capacity: 6,7 - 1500 kW



Fast Delivery