



LOW-TEMP UNIT 25 DX

TECHNICAL SPECIFICATIONS

SPECIFICATIONS

Refrigerant:	R452A
Compressors:	1 x Semi hermetic
Cooling circuits:	1
Ext. controller connection max.:	20 m
max. distance between indoor and outdoor unit:	10 m

COOLING CAPACITY

Cooling capacity:	17 kW - 30 kW
Airflow:	12500 m³/h
Room temperatures:	-10 °C to +5 °C
Cooling capacity room volume:	285 m³ - 1781 m³

DIMENSIONS AND WEIGHT INTERNAL UNIT

Length:	2000 mm
Width:	850 mm
Height:	1100 mm
Empty weight:	590 kg
Forklift Distance:	1100 mm

DIMENSIONS AND WEIGHT EXTERNAL UNIT

Type of electrical connection:	63 A CEE
Max. power consumption:	31.1 kW
Sound pressure in 10m:	46 dB(A)
Length:	2540 mm
Width:	1150 mm
Height:	980 mm
Empty weight:	425 kg
Forklift Distance:	750 mm

ACCESSORIES



Electrical fittings 63A

EQUIPMENT



Electric connector 63A

CHARACTERISTICS



Mobile usability



Plug-and-play System



Low Noise



Service & Leaking tests



24/7 support



Capacity: 6,7 - 1500 kW



Fast Delivery